

Wall mounted unit

FTX-K



Energy saving during standby mode



Online controller via app



Multi model application

Discreet wall mounted unit providing high efficiency and comfort

- › SEER / SCOP up to A++
- › Discreet, stylish front panel blends easily with the wall, and matches all interior décors
- › Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!

- › Online controller (optional): control your indoor from any location with an app, via your local network or internet
- › Dry programme allows humidity levels to be reduced without variations in room temperature

FTX-K + RX-K



Indoor unit		FTX	20K	25K	35K	50K	60K
Casing	Colour		White				
Dimensions	Unit	HeightxWidthxDepth	286x770x225			295x990x263	
Sound power level	Cooling/Heating		55/55		58/58	59/58	60/59
Sound pressure level	Cooling	High/Nom./Low/Silent operation	39/33/25/20	40/33/26/20	43/34/27/20	43/39/34/31	45/41/36/33
	Heating	High/Nom./Low/Silent operation	39/34/28/23	40/34/28/23	43/35/29/26	42/38/33/30	44/40/35/32
Control systems	Infrared remote control		ARC480A11				
	Wired remote control		BRC073 / BRC944B2				



Efficiency data		FTX + RX	20K + 20K	25K + 25K	35K + 35K	50K + 50K	60K + 60K	
Cooling capacity	Min./Nom./Max.	kW	1.3/2.0/2.6	1.3/2.5/3.0	1.3/3.5/4.0	1.7/5.0/6.0	1.7/6.0/7.0	
Heating capacity	Min./Nom./Max.	kW	1.3/2.5/3.5	1.3/3.0/4.0	1.3/4.0/4.8	1.7/6.0/7.7	1.7/7.0/8.0	
Power input	Cooling	Min./Nom./Max.	kW	0.310/0.503/0.720	0.310/0.661/0.720	0.290/1.020/1.3	0.295/1.397/1.542	0.295/1.644/2.255
	Heating	Min./Nom./Max.	kW	0.250/0.524/0.950	0.250/0.688/0.950	0.290/0.995/1.290	0.329/1.579/1.565	0.381/1.929/2.380
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A++				
		Pdesign	kW	2.00	2.50	3.50	5.00	6.00
		SEER		6.66	6.55	6.42	6.59	6.76
	Heating (Average climate)	Annual energy consumption	kWh	105	134	180	266	311
		Energy label		A++			A+	
		Pdesign	kW	2.20	2.40	2.80	4.60	4.80
Nominal efficiency	EER	SCOP		4.65	4.61	4.64	4.10	
		Annual energy consumption	kWh	662	729	845	1,570	1,640
	COP	EER		3.98	3.78	3.4	3.58	3.65
		Annual energy consumption	kWh	4.77	4.36	4.0	3.80	3.63
Energy label	Cooling/Heating		A/A					

Outdoor unit		RX	20K	25K	35K	50K	60K
Dimensions	Unit	HeightxWidthxDepth	550x658x275			735x870x320	
Sound power level	Cooling		60		62	61	63
	Heating		61		62	61	63
Sound pressure level	Cooling	High	46		48	47	49
	Heating	High	47		48	47	49
Operation range	Cooling	Ambient	Min.~Max.	-10~46		-10~46	
	Heating	Ambient	Min.~Max.	-15~18		-15~18	
Refrigerant	Type/GWP		R-410A/2,087.5				
	Charge	kg/TCO ₂ eq	0.74/1.5		1.0/2.1	1.13/2.4	1.45/3.0
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240				

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-025 03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.