



Why choose VRV 5 S-series

RXYSA4-6AV1 / AY1



only
869 mm
high



12.1 kW ~ 15.5 kW



14.2 kW ~ 18.0 kW

VRV 5
BLUEEVOLUTION

SHIRUDO
TECHNOLOGY

1

Sustainability

The solution to reduce the CO₂ footprint of your building

- › Reduced indirect impact thanks to **high seasonal efficiency**
 - › Operational efficiency in real life conditions up to η_{s,c} up to 324.5%
 - › Up to 20% more efficient compared to R-410A model
- › Reduced direct impact thanks to the use of **R-32 refrigerant**
 - › A 71% Global Warming Potential reduction across the entire system compared to R-410A
 - › Single component refrigerant, easy to re-use and recycle
 - › No leak-check requirement according to F-gas (up to 7.4kg of total charge)

-71%

potential global warming impact

Access all technical details here




2

Stretch

Flexible heat pump technology can fit any building, anywhere

- › Low-height single fan range, **only 869mm high**
- › Automatic **ESP up to 45Pa** allows concealed installation
- › Quiet operation via **5 low sound steps**, bringing sound pressure down to 39 dB(A)
- › Easy to handle, thanks to 4 handles
- › Wide access area to reach all key components



3

Smart

Cutting edge technology for smart energy management and accurate comfort control

- › Widest range of **specifically designed indoor units** to match any interior space or design
- › Wide range of connectable controls:
 - › Onecta app with intuitive online and voice control
 - › Intelligent Touch Manager mini BMS



4

Support

Wide network of experts with specialised advice

- › **Maximise BREAAAM/LEED** score thanks to an extra credit and expert support
- › Our online support software with visual floorplan interface makes design easy and ensures compliance with product standards

BREEAM[®]

5

Shîrudo technology

Unparalleled flexibility and peace of mind

- › A fully versatile and responsive system to control the indoor climate of **any room**.
- › **Peace of mind** as no additional considerations or time-consuming studies are needed.
- › **Factory-integrated** refrigerant response measures, compliant with the IEC product standard, third party approved by a notified body.
- › **Easy design and selection** thanks to the integration of VRV Xpress floorplan.
- › With built-in Shîrudo Technology, potential leaks are quickly detected and isolated – **greatly reducing direct emissions impact**.



Daikin Europe N.V. Naamloze Vennootschap Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Publisher)

FSC

ECPEN22-231

05/2022



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Liquid Chilling Packages and Hydronic Heat Pumps, Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

Printed on non-chlorinated paper.