

4-way blow ceiling suspended unit

FXUQ-A



Individual flap
control



Vertical auto swing

Unique Daikin unit for high rooms with no false ceilings nor free floor space

- › Even rooms with ceilings up to 3.5m can be heated up or cooled down very easily without capacity loss
- › Can easily be installed in both new and refurbishment projects
- › Refurbishing the room? Flexibility to suit every room layout without changing the location of

the unit! Via the wired remote controller you can easily control each flap individually and even close the flaps.

- › Reduced energy consumption thanks to specially developed small tube heat exchanger, DC fan motor and drain pump


FXUQ-A



Indoor unit		FXUQ	71A	100A
Cooling capacity	Nom.	kW	8.0	11.2
Heating capacity	Nom.	kW	9.0	12.5
Power input - 50Hz	Cooling	Nom.	0.090	0.200
	Heating	Nom.	0.073	0.179
Dimensions	Unit	Height	198	
		Width	950	
		Depth	950	
Weight	Unit	kg	26	27
Casing	Colour	Fresh White		
	Material	Resin		
Fan-Air flow rate - 50Hz	Cooling	High/Nom./Low	22.5/19.5/16.0	31.0/26.0/21.0
	Heating	High/Nom./Low	22.5/19.5/16.0	31.0/26.0/21.0
Air filter	Type	Resin net with mold resistance		
Sound power level	Cooling	Nom.	-	
Sound pressure level	Cooling	High/Nom./Low	40.0/38.0/36.0	47.0/44.0/40.0
	Heating	High/Nom./Low	40.0/38.0/36.0	47.0/44.0/40.0
Refrigerant	Type/ GWP	R-410A / 2.087,5		
Piping connections	Liquid	OD	9.52	
	Gas	OD	15.9	
	Drain		I.D. 20/O.D. 26	
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/60/220-240/220-230	
Current - 50Hz	Maximum fuse amps (MFA)	A	16	
Control systems	Infrared remote control	BRC7C58		
	Simplified wired remote control for hotel applications	-		
	Wired remote control	BRC1E52A/B / BRC1D52		

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-247

02/15



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.